

Reliable

Model TNL280 Pendent Spray Nozzle
Designed primarily for use in tunnel fire protection

K28.0 (400 Metric)
cULus Listed

Product Features

- cULus Corrosion Resistant Nozzle
- Distribution criteria for coverage up to 324 ft² (30.25 m²) per nozzle

Product Description

The Reliable Model TNL280 is a cULus Listed nonautomatic (open) spray nozzle for use in fixed fire protection systems. The Model TNL280 nozzle is intended for installation in the pendent position. The nozzle has an Electroless Nickel PTFE (ENT) finish and is cULus Listed as Corrosion Resistant. Verify compatibility with the environment where the nozzle will be located prior to installation.



Application

The Model TNL280 nozzle is intended to be installed in accordance with NFPA 15. cULus Listed spray distribution and water spray density information are provided in Figure 2 and Table A, respectively, of this Bulletin. Water spray systems, including those used as tunnel fire protection systems, should only be designed by experienced fire protection system designers who understand the characteristics and limitations of all products used as part of the water spray system. The fire protection system designer should consider factors that may impact the performance of the water spray system, including, but not limited to, the fire hazard, surrounding construction, nozzle location, obstructions, and the effect of natural or mechanical ventilation.

Listings and Approvals

Listed by Underwriters Laboratories, Inc. and UL Certified for Canada (cULus)

UL Listing Category

Nozzles, Spray Type, Fixed

UL Guide Number

VGYZ

Listed Water Spray Density for Installation from 17 ft to 20 ft (5.2 m to 6.1 m) above Finished Floor			Table A
Coverage Area ft x ft (m x m)	Flow Rate gpm (L/min)	Operating Pressure psi (bar)	Average Water Spray Density over the Coverage Area* gpm/ft² (mm/min)
18 x 18 (5.5 x 5.5)	75 (285)	7 (0.5)	0.217 (8.8)
18 x 18 (5.5 x 5.5)	125 (475)	20 (1.4)	0.37 (15.0)

*Listed to provide +/- 15% of the Average Water Spray Density over the Coverage Area under test conditions specified in UL 2351.

Model TNL280 Spray Nozzle

Technical Specifications

Style: Pendent, Open Nozzle

Threads: 1" NPT or ISO7-1R1

Nominal K-Factor: 28.0 (400 metric)

Max. Working Pressure: 175 psi (12 bar)

Min. Working Pressure: 7 psi (0.48 bar)

Material Specifications

Nozzle Frame: Brass Alloy

Deflector Screw Retainer: Bronze Alloy

Deflector: Bronze Alloy

Nozzle Finish

Electroless Nickel PTFE (ENT)

Wrench

Model N1


Listings and Approvals

cULus Listed




Model TNL280 Pendent Spray Open Nozzle Components and Dimensions

Figure 1



Model TNL280 Pendent Spray Pattern Graph

Figure 2



Wrench



Model N1

Installation

Model TNL280 nozzles are intended to be installed in accordance with NFPA 15, as well as the requirements of applicable Authorities Having Jurisdiction. Model TNL280 nozzles must be handled carefully. Nozzles should be stored in the original packaging until installed. Handle nozzles only by the frame and not by the deflector. Nozzles that are visibly damaged should not be installed.

Install the Model TNL280 nozzle by applying PTFE-based thread sealant to the male threads of the nozzle. Thread the nozzle into the sprinkler system fitting by hand, then tighten the nozzle using only the Reliable Model N1 wrench. The Reliable Model N1 wrench is designed to engage the nozzle's wrench flats; do not wrench any other part of the nozzle.

Recommended installation torque is 22 to 30 ft/lb (30 to 40 N/m). Do not exceed the maximum recommended torque. Exceeding the maximum torque may damage and impair the performance of the nozzle.

Maintenance

Reliable Model TNL280 should be inspected and the system maintained in accordance with NFPA 25, as well as the requirements of any Authorities Having Jurisdiction.

It is recommended that the water spray system be inspected by an authorized technical personnel. The nozzle must be checked for physical damage, corrosion, external and internal obstruction, and blockage if any. The nozzle should be cleared or replaced if required.

The owner is solely responsible for maintaining the water spray system and components therein, so that it performs properly in actual conditions.

Guarantee

For the Reliable Automatic Sprinkler Co., Inc. guarantee, terms, and conditions, visit www.reliablesprinkler.com.

Patents

Patent Pending

Ordering Information

Specify the following when ordering.

Nozzle

- Model TNL280

Threads

- NPT
- ISO 7-1

Wrench

- Model N1